

# DTK-1651



## DTK-1651

The DTK-1651 is the premium pen display for eDocuments which allows documents to be viewed, edited and signed in portrait mode without shrinking or scrolling or landscape mode. Slim. Innovative. Functional.

### Best-in-class for comfort and security.

The DTK-1651 combines a 15.6" Full HD resolution LCD display with state-of-the-art encryption. Its slim, sleek design leaves only a small footprint. With only one cable, the DTK-1651 eliminates cable clutter, the innovative pen holder and pen compartment create a convenient use.

- View and sign full-sized documents in A4 or Letter Size
- Convertible to portrait and landscape modes, flat on desk or 15° build-in stand
- 3-in-1 cable for power, HDMI and USB

### Use case scenarios for eDocuments

Wacom's DTK-1651 is the premium product for banking, finance or insurance, education and healthcare, hospitality, telecoms or other POS retail solutions, the DTK-1651 is the top-class product for all situations where the full document needs to be displayed for signing. The DTK-1651 can be easily integrated into existing infrastructure.

Accessories/spare parts are available separately, like stand with VESA adapter, Pen, 3-in-1 cable, VGA-HDMI adapter, HDMI-VGA adapter, Pen nib set, Pen tether, AC adapter



## DTK-1651

**General Specifications**

Dimensions(W x H x D, excluding stand)	0 x 286 x 17mm
Weight (including stand)	2.0 kg
Stand inclination	15°
Stand inclination	egrated stand (landscape 15°/portrait 15°)
Power consumption	2 VDC, 3A (max)
Supported operating systems	Windows 10/8.1/8/7 (32-bit, 64-bit) Mac OSX 10.9 and later

**LCD Display**

Display	IPS
Cover glass surface	Anti-glare etched glass
Screen diagonal	15.6" (344.16 x 193.59 mm)
Resolution	ll HD, 1920 x 1080 pixels
Viewing angles (horizontal/vertical)	170° / 170°
Luminance (brightness)	200 cd/m <sup>2</sup> (typical)
Contrast ratio	800:1 (typical), 600:1 (min)
Response time	30 ms (typical)
Backlight lifetime	25.000 hours

**Tablet and pen**

Technology	Electromagenetic Resonance (EMR)
Active area	346.16 x 195.59 mm
Resulotion	2,540 lpi
Coordinate accuracy	±0.5 mm
Pressure levels	1,024

**Miscellaneous**

Reading height	5 mm or more (center)
Wall mount	VESA 75 mm
Software	compatible with signature / E-signing software and Wacom's sign pro PDF
Package content	interactive pen display with integrated stand, cordless and battery-free pen, 3-in-1 cable (1.8 m/ 5.91 ft), installation CD (Wacom driver, product information), quick start guide, pen tether, (nylon fiber, 50 cm / 19.7 inch), 5 extra nibs, nib removal tool, power supply, power cable
Operating temperature, relative humidity	5 to 40 degrees C, Humidity: 30% to 80% RH (non-condensing)
Storage temperature, relative humidity	-10 to 60 degree C, Humidity: 20% to 90% RH (non-condensing)(Maximum storage humidity is 38% at a temperature of 60 degree C, and maximum storage temperature is 42 degree C at a humidity of 90%.)
Warranty	3 years (WTC, WEG)1 year (WAP, WJP, WCN)