

# STU-300B

wacom®  
for Business

## STU-300B

With its small and compact design in combination with its durable and robust quality, the STU-300B LCD signature pad is ideally suited for professionals who work with eDocuments.



The STU-300B enables to capture handwritten electronic signatures without having to print off hardcopies. This will boost the workflow efficiency significantly: customers will be able to sign contracts, approve payments and confirm deliveries quickly and securely – without any paper documents.

- Used flat on desk or counter to capture handwritten digital signatures
- High resolution and superior accuracy
- Anti-glare etched glass for a natural, paper-like feel
- AES128bit/DH encryption for secure data transfer

### Use case scenarios for eSignature

Wacom's STU-300B is ideal for transactions at banks, insurance agents working in the field or credit card sales at Point-of-Sale. While the customer is viewing the document on a laptop or PC monitor, the signature will be captured on the STU-300B for approving the transaction.

## General Specifications

Overall Dimensions	156 x 126.86 x 16.9 mm (6.1 x 5 x 0.7 Inch)
Weight	200 g
Main body color	Black
Power supply	USB bus powered
Power consumption	1.0 W maximum
Communication interface	USB

## LCD Display

Display Type	Monochrome, reflective FSTN
Cover plate surface	Anti glare
Screen Size	98.985 x 24.985 cm (3.99 x 0.98inch)
Native Resolution	396 x 100 pixels

## Pad and pen

Reading Technology	Electromagnetic Resonance (EMR)
Active area	98.98 x 24.98 cm (3.99 x 0.98inch)
Coordinate Resolution	2,540 lpi (not interpolated)
Coordinate accuracy	± 0.5 mm / 0.02 inch (center)
Pen Report Rate	200 points per second (non-interpolated)
Pen Pressure Levels	512 (non-interpolated)
Encryption	AES128bit/DH

## Miscellaneous

Pen Storage	Pen holder
Connectivity security	USB cable locking system
Data security	Real time signature capture without internal pad memory
Security Lock Slot	No
Software	Compatible with signature / E-signing software and Wacom sign pro PDF
Package content	Signature pad, cordless and battery-free pen, USB cable (3 m / 9.84 ft), quick start guide, pen tether (nylon fiber, 50 cm / 19.7 inch), USB plug attachment, regulation sheet
Operating temperature, relative humidity	+5°C to +40°C, +41°F to +104°F, (humidity 30% to 80% RH, no condensing)
Storage temperature, relative humidity	-20°C to +60°C, -4°F to +140°F, (humidity 30% to 90% RH, no condensing)
Warranty	1-3 years depending on region and channel of purchase.

